



## Pure Clean Waste Solutions Ltd - Risk Assessment

Scope of Assessment: Service Engineers - Service of Parts Washer – Std/Large

Reviewed & Updated: January 2012

Persons Present: Matt Smith & Karen Jones

Page 1 of 1

Significant Hazard	Process	Who is at Risk	Initial Risk			Control Measures	Residual Risk			Action Point
			Lk	Sv	R		Lk	Sv	R	
Chemical / C.O.S.H.H.	1. Moving and lifting containers containing potentially Hazardous Waste and Fresh Product. 2. Specific hazard from solvent	1. Service Engineer	4	4	16	1. Exposure is regulated by use of correct PPE which is randomly inspected. Specifically Service Engineers are instructed to wear full overalls, eye protection and impervious gloves at all times whilst the machine is serviced. 2. Overalls are regularly cleaned (spare overalls are kept in the vehicle for emergency use). 3. Full training is given to all Service Engineers on the correct use of PPE and handling techniques. 4. Written information is also provided for Service Engineers to refer to if necessary (Driver Handbook – Method Statement).	2	2	4	Conduct regular Driver Appraisals to assess correct use of PPE equipment used by Engineer
Manual Handling	Pushing, pulling, bending & lifting when: - 1. Moving / loading / unloading barrels and containers.	1. Service Engineer	8	4	32	1. All Service Engineers are issued with, and trained in the use of appropriate trolleys (sack trolley) which limit manual handling. 2. This equipment is randomly inspected. 3. The operation involved in connecting the Parts Washer to a new drum of Solvent can only be performed manually without the use of lifting aids due to the physical lack of space and the dangers involved in using this equipment. The process is high risk therefore the correct Manual Handling Techniques must be adhered to. 4. If the working environment limits the safe Manual Handling of this task the Operators are asked to seek assistance (see Working Environment). 5. All Service Engineers are issued with and periodically tested on written instructions contained within the Driver Handbook. 6. MAC Assessment indicates the Manual Handling Hazards to be Medium Risk – refer to score sheet for further information.	2	2	4	Monitor during Driver Appraisals
Fire / Explosion	Hazardous materials handled and carried on vehicle.	1. Service Engineer 2. Customer 3. General Public	6	8	48	1. All Service Engineers handling or carrying hazardous waste have ADR training including fire-fighting training. 2. All Vehicles are equipped with the correct Fire Fighting equipment as required by VOSA. The vehicles are regularly check to ensure the equipment is present and in date. 3. Written Instructions (Driver Handbook) have been issued to all Service Engineers prohibiting smoking at all times	2	2	4	Monitor during Driver Appraisals
Spills	Exposure to chemicals (solvents, oils, battery acid)	1. Service Engineer 2. Customer	6	4	24	1. The risk of spillage is minimised by the correct handling techniques and training given to all Service Engineers. 2. Any spill to be cleared immediately using absorbents Carried on their vehicle. 3. Spillage Training is conducted on a regular basis -see Training Schedule. 4. Clear written instructions - Emergency / Spillage Procedure (Method) and Clean-up Spillage Procedure (Method) are provided for the Service Engineers to refer to in the Driver Handbook. 5. Customer to be informed immediately of any incident involving a spillage.	2	2	4	Ensure Training sessions are conducted regularly
Working Environment	Safe working Environment.	1. Service Engineer	6	4	36	1. Service Engineers trained to seek appropriate person on site at customers premises and to ask for site specific information regarding safety where relevant and to observe customers own site regulations. 2. All instructions are in Driver Handbook for reference. 3. Service Engineers inform an appropriate member of staff on site that he is about to enter the area where the service is to take place. 20 minutes is set aside for a standard service. 4. If the condition of the machine is unusually bad the Engineer will contact his line Manager within 30 minutes of entering the site to seek further advice. 5. The Service Engineer must ensure a safe working area is provided before the service commences (6ft square clear and safe working area).	2	2	4	
Working Hazards: a) Falls, Trips and Slips	1. Limited working environment 2. Spills 3. Trips from cables etc.	1. Service Engineer	8	4	32	1. Service Engineers aware of need to maintain awareness of floor conditions with regard to spills and equipment. 2. Specific training provided to ensure Service Engineers understand the consequences of poor floor conditions so that they are continually aware and focused on the need to maintain good floor conditions with regard to spills and their equipment. 4. Written instructions have been issued to all Service Engineers to clean up any spills immediately to ensure safe working environment.	2	2	4	
b) Noise	Noise from machinery used whilst on customers site.	1. Service Engineer	6	4	24	1. All Service Engineers are fully trained in all the correct PPE that must be worn during certain operations. 2. When working on site where high levels of noise exist (see signage) Service Engineers are provided with and instructed to wear ear defenders / disposable ear protectors at all times.	2	2	4	
c) Dust / Fumes	Dust / Fumes from machinery used whilst on customers site.	1. Service Engineer	6	4	24	1. All Service Engineers are fully trained in all the correct PPE that must be worn during certain operations. 2. When working on site where high levels of dust/fumes exist (see signage) Service Engineers are provided with and instructed to wear suitable face masks at all times.	2	2	4	
d) Vehicle Movement	Danger from moving vehicles including fork lift trucks.	1. Service Engineer 2. Customer 3. Other site users	6	4	24	1. Work areas are clearly defined with client/customer. 2. Service Engineer instructed to use banks person if visibility is restricted when reversing on customer site.	2	2	4	
e) Projectiles	Possibility of small fragments being thrown from machinery whilst on customers site.	1. Service Engineer	2	4	8	1. All Service Engineers are fully trained in all the correct PPE that must be worn during certain operations. 2. When working on site where high levels of noise exist (see signage) Service Engineers are provided with and instructed to wear ear defenders at all times.	2	2	4	
f) Electricity	Operation of electrical machinery / equipment as part of customers site operations.	1. Service Engineer	2	4	8	1. Awareness of existing site regulations.	2	2	4	

**LIKELIHOOD (Chance of Occurrence)**

2 Unlikely  
4 Possibility  
6 Very Likely  
8 Certainty

**SEVERITY (Outcome)**

2 Minor Injury  
4 Major Injury or Disability  
6 Death  
8 Multiple Deaths

Risk evaluation: - Likelihood (Lk) x Consequence = Risk, Defined as High (36-64), Medium (9-35) or Low (4-8)