

SAFETY DATA SHEET

STANDARD THINNERS

1 IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: STANDARD THINNERS
Product code: Material 80001910
Company name: Pure Clean Waste Solutions Ltd
 Old Moor Road,
 Bredbury,
 Stockport,
 SK6 2QE
Tel: 0161 430 5390
Fax: 0161 406 9723
Email: support@pcws.co.uk
Emergency Tel: 0161 430 5390

2 HAZARDS IDENTIFICATION

Classification of the substance or mixture:
 Classification (EC 1272/2008)
 Physical and Chemical Hazards Flam. Liq. 2 - H225
 Human health Acute Tox. 4 - H302; Acute Tox. 4 - H312; Acute Tox. 4 - H332; Skin Irrit. 2 - H315; Eye Dam. 1 - H318; Repr. 2 - H361fd; STOT SE 2 - H371; STOT RE 2 - H373; Asp. Tox. 1 - H304
 Environment Aquatic Chronic 2 - H411
 Classification (1999/45/EEC) Xn; R20/21/22, R68/20/21/22, R48/20, R65. Repr. Cat. 3; R62, R63. Xi; R38, R41. F; R11. N; R51/53.
 The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.
 Human health Vapours may irritate the respiratory system and cause coughing, asthmatic breathing and breathlessness. Irritating to eyes.
 Environment The product contains a substance which is toxic to aquatic organisms.
Label elements: Contains HEXANE-norm
 METHANOL
 TOLUENE

Label In Accordance With (EC) No. 1272/2008



Signal Word Dang
Hazard Statements H225 Highly flammable liquid and vapour.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H332 Harmful if inhaled.
 H361fd Suspected of damaging fertility or the unborn child.
 H371 May cause damage to organs .
 H373 May cause damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.
Precautionary Statements P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P240 Ground/bond container and receiving equipment.
 P243 Take precautionary measures against static discharge.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P281 Use personal protective equipment as required.
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P322 Specific measures (see medical advice on this label).
 P501a Dispose of container to a licensed disposal site



SAFETY DATA SHEET

STANDARD THINNERS

2 HAZARDS IDENTIFICATION cont.

Label elements continued:

Signal Word	Danger
Supplementary Precautionary Statements	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P233 Keep container tightly closed. P241 Use explosion-proof electrical equipment. P242 Use only non-sparking tools. P270 Do not eat, drink or smoke when using this product. P260 Do not breathe vapour/spray. P261 Avoid breathing vapour/spray. P264 Wash contaminated skin thoroughly after handling. P321 Specific treatment (see medical advice on this label). P370+378 In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction. P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301+312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. P302+352 IF ON SKIN: Wash with plenty of soap and water. P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P308+313 IF exposed or concerned: Get medical advice/attention. P309+311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician. P310 Immediately call a POISON CENTER or doctor/physician. P312 Call a POISON CENTER or doctor/physician if you feel unwell. P314 Get medical advice/attention if you feel unwell. P330 Rinse mouth. P331 Do NOT induce vomiting. P332+313 If skin irritation occurs: Get medical advice/attention. P362 Take off contaminated clothing and wash before reuse. P363 Wash contaminated clothing before reuse. P391 Collect spillage. P403+235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

3 COMPOSITION / INFORMATION ON INGREDIENTS

Mixtures:

ACETONE	1-5%
CAS-No.:	67-64-1 EC No.: 200-662-2 Registration Number: LG248292-42 Pre Registration
Classification (EC 1272/2008)	Classification (67/548/EEC)
Flam. Liq. 2 - H225	F;R11
EUH066	Xi;R36
Eye Irrit. 2 - H319	R66
STOT SE 3 - H336	R67
BUTAN 2-OL	5-10%
CAS-No.: 78-92-2	EC No.: 201-158-5
Classification (EC 1272/2008)	Classification (67/548/EEC)
Flam. Liq. 3 - H226	R10
Eye Irrit. 2 - H319	Xi;R36/37
STOT SE 3 - H335	R67
STOT SE 3 - H336	



SAFETY DATA SHEET

STANDARD THINNERS

3 COMPOSITION / INFORMATION ON INGREDIENTS cont.

Mixtures continued:

BUTANOL-norm 5-10%
CAS-No.: 71-36-3 EC No.: 200-751-6 Registration Number: VT248480-07 Pre-Registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 3 - H226 R10
Acute Tox. 4 - H302 Xn;R22
Skin Irrit. 2 - H315 Xi;R37/38,R41
Eye Dam. 1 - H318 R67
STOT SE 3 - H335
STOT SE 3 - H336

BUTANONE 1-5%
CAS-No.: 78-93-3 EC No.: 201-159-0 Registration Number: BF251801-58 Pre-Registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 2 - H225 F;R11
EUH066 Xi;R36
Eye Irrit. 2 - H319 R66
STOT SE 3 - H336 R67

BUTYL ACETATE norm 1-5%
CAS-No.: 123-86-4 EC No.: 204-658-1 Registration Number: AT248515-23 Pre-Registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 3 - H226 R10
EUH066 R66
STOT SE 3 - H336 R67

CYCLOHEXANE 5-10%
CAS-No.: 110-82-7 EC No.: 203-806-2 Registration Number: NW773949-79 Pre-registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 2 - H225 F;R11
Skin Irrit. 2 - H315 Xn;R65
STOT SE 3 - H336 Xi;R38
Asp. Tox. 1 - H304 R67
Aquatic Acute 1 - H400 N;R50/53
Aquatic Chronic 1 - H410

ETHANOL 5-10%
CAS-No.: 64-17-5 EC No.: 200-578-6

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 2 - H225 F;R11

ETHYL ACETATE 1-5%
CAS-No.: 141-78-6 EC No.: 205-500-4 Registration Number: YZ252117-95 Pre-Registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 2 - H225 F;R11
EUH066 Xi;R36
Eye Irrit. 2 - H319 R66
STOT SE 3 - H336 R67

ETHYLBENZENE 5-10%
CAS-No.: 100-41-4 EC No.: 202-849-4

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 2 - H225 F;R11
Acute Tox. 4 - H332 Xn;R20



SAFETY DATA SHEET

STANDARD THINNERS

3 COMPOSITION / INFORMATION ON INGREDIENTS cont.

Mixtures continued:

HEPTANE 5-10%
CAS-No.: 142-82-5 EC No.: 205-563-8 Registration Number: FS259067-18 Pre-Registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 2 - H225 F;R11
Skin Irrit. 2 - H315 Xn;R65
STOT SE 3 - H336 Xi;R38
Asp. Tox. 1 - H304 R67
Aquatic Acute 1 - H400 N;R50/53
Aquatic Chronic 1 - H410

HEXANE-norm 5-10%
CAS-No.: 110-54-3 EC No.: 203-777-6 Registration Number: TB252081-55 Pre-Registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 2 - H225 F;R11
Skin Irrit. 2 - H315 Repr. Cat. 3;R62
Repr. 2 - H361f Xn;R48/20,R65
STOT SE 3 - H336 Xi;R38
STOT RE 2 - H373 R67
Asp. Tox. 1 - H304 N;R51/53
Aquatic Chronic 2 - H411

METHANOL 1-5%
CAS-No.: 67-56-1 EC No.: 200-659-6 Registration Number: NX251535-05 Pre-Registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 2 - H225 F;R11
Acute Tox. 3 - H301 T;R23/24/25,R39/23/24/25
Acute Tox. 3 - H311
Acute Tox. 3 - H331
STOT SE 1 - H370

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

METHYL ACETATE 1-5%
CAS-No.: 79-20-9 EC No.: 201-185-2 Registration Number: NF251828-30 Pre-Registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 2 - H225 F;R11
EUH066 Xi;R36
Eye Irrit. 2 - H319 R66
STOT SE 3 - H336 R67

MIBK 1-5%
CAS-No.: 108-10-1 EC No.: 203-550-1

Classification (EC 1272/2008) Classification (67/548/EEC)
Not classified. Xn;R20/21/22.
Xi;R36/37/38.
F;R11.

PROPAN-1-OL 5-10%
CAS-No.: 71-23-8 EC No.: 200-746-9 Registration Number: AB251662-53 Pre-registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 2 - H225 F;R11
Eye Dam. 1 - H318 Xi;R41
STOT SE 3 - H336 R67

PROPAN-2-OL 5-10%
CAS-No.: 67-63-0 EC No.: 200-661-7 Registration Number: VP266085-11 Pre-registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 2 - H225 F;R11
Eye Irrit. 2 - H319 Xi;R36
STOT SE 3 - H336 R67



SAFETY DATA SHEET

STANDARD THINNERS

3 COMPOSITION / INFORMATION ON INGREDIENTS cont.

Mixtures continued:

PROPYL ACETATE 1-5%
CAS-No.: 109-60-4 EC No.: 203-686-1 Registration Number: QP252031-35 Pre-registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 2 - H225 F;R11
EUH066 Xi;R36
Eye Irrit. 2 - H319 R66
STOT SE 3 - H336 R67

TETRAHYDROFURAN 1-5%
CAS-No.: 109-99-9 EC No.: 203-726-8 Registration Number: LC252053-60 Pre-Registration

Classification (EC 1272/2008) Classification (67/548/EEC)
EUH019 F;R11,R19
Flam. Liq. 2 - H225 Xi;R36/37
Eye Irrit. 2 - H319
STOT SE 3 - H335

TOLUENE 10-30%
CAS-No.: 108-88-3 EC No.: 203-625-9 Registration Number: DW252005-29 Pre-Registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 2 - H225 F;R11
Skin Irrit. 2 - H315 Repr. Cat. 3;R63
Repr. 2 - H361d Xn;R48/20,R65
STOT SE 3 - H336 Xi;R38
STOT RE 2 - H373 R67
Asp. Tox. 1 - H304

XYLENE 5-10%
CAS-No.: 1330-20-7 EC No.: 215-535-7 Registration Number: NC259393-41 Pre-Registration

Classification (EC 1272/2008) Classification (67/548/EEC)
Flam. Liq. 3 - H226 R10
Acute Tox. 4 - H312 Xn;R20/21
Acute Tox. 4 - H332 Xi;R38
Skin Irrit. 2 - H315

Composition Comments:

This preparation may vary in composition, but typically may contain some or all of the above.

4 FIRST AID MEASURES

General information: Remove affected person from source of contamination. NOTE! Keep affected person away from heat, sparks and flames! If breathing stops, provide artificial respiration. Get medical attention.
Skin contact: Immediately remove contaminated clothing. Wash skin thoroughly with soap and water for several minutes. Contact physician if irritation continues.
Eye contact: Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Continue flushing during transport to hospital. Bring these instructions.
Ingestion: Get medical attention immediately! Remove victim immediately from source of exposure. DO NOT INDUCE VOMITING! Drink plenty of water. Never give liquid to an unconscious person.
Inhalation: Remove victim immediately from source of exposure. Place unconscious person on the side in the recovery position and ensure breathing can take place. If breathing stops, provide artificial respiration. Get medical attention.

5 FIRE-FIGHTING MEASURES

Extinguishing media: Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.
Special hazards arising from the substance or mixture
Unusual Fire & Explosion Hazards: Forms explosive mixtures with air. HIGHLY FLAMMABLE!
Specific hazards: Vapours are heavier than air and may travel along the floor and in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember. The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.
Advice for firefighters
Special Fire Fighting Procedures: Be aware of risk of fire re-starting, and risk of explosion. Avoid breathing fire vapours.
Protection of fire-fighters: Self contained breathing apparatus and full protective clothing must be worn in case of fire



SAFETY DATA SHEET

STANDARD THINNERS

6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:
Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with eyes and prolonged skin contact. Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area.

Environmental precautions:
Do not discharge into drains, water courses or onto the ground. Avoid discharge to the aquatic environment. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body. Contain spillages with sand, earth or any suitable adsorbent material.

Methods and material for containment and cleaning up:
Ventilate well, stop flow of gas or liquid if possible. Remove ignition sources. Do not allow chemical to enter confined spaces such as sewers due to explosion risk. Sewers designed to preclude formation of explosive concentrations of vapour may be permitted. Absorb in vermiculite, dry sand or earth and place into containers.
For waste disposal contact Pure Clean Waste Solutions Ltd to dispose of contaminated absorbent material in line with regulations – see section 13.

7 HANDLING AND STORAGE

Handling requirements: Avoid spilling, skin and eye contact. Eliminate all sources of ignition. Eye wash facilities and emergency shower must be available when handling this product. Do not use in confined spaces without adequate ventilation and/or respirator.

Storage conditions: Store in a cool and well-ventilated place. Take precautionary measures against static discharges.

Storage Class: Flammable liquid storage.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Name	Std	TWA - 8 Hrs		STEL - 15 Min		Notes
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3	
BUTAN-2-OL	WEL	100 ppm	308 mg/m3	150 ppm	462 mg/m3	
BUTANOL-norm	WEL			50 ppm(Sk)	154mg/m3(Sk)	
BUTANONE	WEL	200 ppm(Sk)	600mg/m3(Sk)	300ppm(Sk)	899mg/m3(Sk)	
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3	
CYCLOHEXANE	WEL	100 ppm	350 mg/m3	300 ppm	1050 mg/m3	
ETHANOL	WEL	1000 ppm	1920 mg/m3			
ETHYL ACETATE	WEL	200 ppm		400 ppm		
ETHYLBENZENE	WEL	100ppm(Sk)	441mg/m3(Sk)	125ppm(Sk)	552mg/m3(Sk)	
HEPTANE	WEL	500 ppm				
HEXANE-norm	WEL	20 ppm	72 mg/m3			
METHANOL	WEL	200ppm(Sk)	266mg/m3(Sk)	250ppm(Sk)	333mg/m3(Sk)	
METHYL ACETATE	WEL	200 ppm	616 mg/m3	250ppm	770 mg/m3	
PROPAN-1-OL	WEL	200ppm(Sk)	500mg/m3(Sk)	250ppm(Sk)	625mg/m3(Sk)	
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	
PROPYL ACETATE	WEL	200 ppm	849 mg/m3	250 ppm	1060 mg/m3	
TETRAHYDROFURAN	WEL	50 ppm(Sk)	150mg/m3(Sk)	100ppm(Sk)	300mg/m3(Sk)	
TOLUENE		\ ppm(Sk)	1mg/m3(Sk)	< 0 ppm(Sk)	4mg/m3(Sk)	
XYLENE	WEL	50 ppm(Sk)	220mg/m3(Sk)	100ppm(Sk)	441mg/m3(Sk)	

WEL = Workplace Exposure Limit.
mg/m3(Sk)

SAFETY DATA SHEET

STANDARD THINNERS


8 EXPOSURE CONTROLS / PERSONAL PROTECTION cont.


Protective equipment

Process conditions: Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash, quick drench.

Engineering measures: Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Respiratory equipment: If ventilation is insufficient, suitable respiratory protection must be provided.

Hand protection: Wear protective gloves. 

Eye protection: Wear approved safety goggles. 

Other Protection: Provide eyewash station and safety shower. Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures: Wash promptly with soap & water if skin becomes contaminated. Wash contaminated clothing before reuse.

Personal protection: Where the risk of exposure exists, such as tanker loading/ unloading, non routine operations or emergency circumstances the above Personal Protection measures are recommended.

Skin protection: Overall or lab coat

9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance: Clear liquid.

Colour: Colourless.

Initial boiling point and boiling range: 55-160 760 mm Hg

Relative density: 0.8-0.9 20

Flash point: -20 (acetone) CC (Closed cup).

Auto Ignition Temperature(°C): >203

Flammability Limit - Lower(%): 1

Flammability Limit - Upper(%): 36.5

10 STABILITY AND REACTIVITY

Chemical stability: Stable under normal temperature conditions and recommended use.

Possibility of hazardous reactions: Hazardous Polymerisation
Will not polymerise

Conditions to avoid: Avoid heat, flames and other sources of ignition.

Materials to avoid: Strong oxidising substances.

Haz. decomp. products: During fire, toxic gases (CO, CO2) are formed.

11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxic Dose 1 - LD 50
28710 mg/kg (oral rat)

Toxic Conc. - LC 50
48000 ppm/4h (inh-rat)

Inhalation: Vapours may irritate the respiratory system and cause coughing, asthmatic breathing and breathlessness. In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects.

Ingestion: Harmful: possible risk of irreversible effects if swallowed.

Skin contact: Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Eye contact: May cause severe irritation to eyes.

SAFETY DATA SHEET

STANDARD THINNERS

11 TOXICOLOGICAL INFORMATION cont.

Health Warnings: May cause unconsciousness, blindness and possibly death. Repeated exposure may cause chronic eye irritation. May cause chemical eye burns. Acute eczematous dermatitis, contact type erythema, oedema, papules, vesicles, bullae, crusts, desquamation. Swallowing concentrated chemical may cause severe internal injury.

Route of entry: Inhalation. Ingestion.

Target Organs: Central nervous system Eyes

Medical Symptoms: Irritation of eyes and mucous membranes. Unconsciousness.

Medical Considerations: Pre Existing Respiratory Disorders and Lung Diseases.

Specific effects: May cause damage to the liver and kidneys.

12 ECOLOGICAL INFORMATION

Mobility in soil

Mobility: The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Other adverse effects: The product contains a substance which is very toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS

General information: If this product becomes waste it is to be treated as hazardous waste. Any other constituents or contaminants in the waste stream must be taken into account when classifying the waste. In the EU, the European Waste Catalogue Code to be assigned is dependant on the processes giving rise to the waste. In the absence of any such processes having taken place EWC 140603* (other solvents and solvent mixtures) may be used. Hazardous waste must be suitably contained, stored, packaged and transported, see section 7 and 4 for such details. In the UK only waste carriers registered with the Environment Agency may transport waste.

Waste treatment methods: Waste and residues must be disposed of in accordance with national regulatory requirements. Suitably permitted or licensed recycling or recovery sites should be used for disposal. Contact PCWS Ltd for such services (see Section 1). If recycling/recovery is not possible, disposal by suitably high temperature incineration is an alternative.

14 TRANSPORT INFORMATION

UN number

UN No. (ADR/RID/ADN): 1263

UN No. (IMDG): 1263

UN No. (ICAO): 1263

Transport hazard class(es)

ADR/RID/ADN Class: 3

IMDG Class: 3

ICAO Class/Division: 3

Transport Labels



Packing group

ADR/RID/ADN Packing group: II

IMDG Packing group: II

ICAO Packing group: II

Proper Shipping name: PAINT or PAINT RELATED MATERIAL

Environmental hazards

Environmental hazards: Environmentally Hazardous Substance/Marine Pollutant

Special precautions for user: Emergency Action Code 3YE

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code





SAFETY DATA SHEET

STANDARD THINNERS

15 REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture
Chemical Safety Assessment

16 OTHER INFORMATION

General information: Please ensure that this Safety Data Sheet is passed onto the relevant person(s) in your company, who are capable of acting on the information given.

Information Sources: Material Safety Data Sheet, Misc. manufacturers.

Risk Phrases In Full: R10 Flammable.
R20/21 Harmful by inhalation and in contact with skin.
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R20 Harmful by inhalation.
R22 Harmful if swallowed.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R65 Harmful: may cause lung damage if swallowed.
R68/20/21/22 Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.
R11 Highly flammable
R36/37 Irritating to eyes and respiratory system.
R36/37/38 Irritating to eyes, respiratory system and skin.
R36 Irritating to eyes.
R37/38 Irritating to respiratory system and skin.
R38 Irritating to skin.
R19 May form explosive peroxides.
R63 Possible risk of harm to the unborn child.
R62 Possible risk of impaired fertility.
R66 Repeated exposure may cause skin dryness or cracking.
R41 Risk of serious damage to eyes.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R67 Vapours may cause drowsiness and dizziness.
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Hazard Statements In Full: EUH019 May form explosive peroxides.
EUH066 Repeated exposure may cause skin dryness or cracking.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H361f Suspected of damaging fertility.
H361fd Suspected of damaging fertility or the unborn child.
H370 Causes damage to organs.
H371 May cause damage to organs.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Pure Clean Waste Solutions Ltd shall not be held liable for any damage resulting from handling or from contact with the above product.